

# PENBERTHY

## general information

Section 100  
Standard Stock 103  
Issued 11/03  
Replaces 6/99

For: STANDARD PRODUCT

---

### STANDARD PRODUCT

#### Level Gages:

RL, TL, RM, TM, RH & TH Model Gages

Sections: One through three, L & M series. One through three H series  
Glass Size: Four through nine, L & M series. Four through nine H series  
Wetted: Carbon Steel or 304/304L, 316/316L Stainless Steel  
Cover: Iron, Carbon Steel and 304/304L, 316/316L Stainless Steel  
Connections: 1/2" or 3/4" NPTF, 1/2" Socketweld  
Hardware: A193 B7 bolting / A194 Gr 2 or 2H nuts  
Glass: Tempered Borosilicate Sizes 1 to 9 reflex & transparent  
Gaskets: Grafoil® / Mylar insert, Nobestos®, Teflon®  
Cushions: Grafoil® / Mylar insert, Nobestos®, Teflon®  
Paint: Standard

#### Armored Valves:

Models: 320, 330, 420, 430, 720, and 730

Wetted: A105 CS Body or 316 SS Body  
Trim: Stainless Steel  
Connections: 1/2 x 1/2 x 1/2, 3/4 x 1/2 x 1/2, 3/4 x 3/4 x 1/2  
Packing: Grafoil® or Teflon®

#### Tubular Valves:

Models: N7A and N7B

Wetted: Carbon Steel, Iron, Bronze, & Stainless Steel

#### Sight Flow Indicators:

Models: SF, SFF, SFD & SFR

Wetted: Iron, Carbon Steel, and 316 Stainless Steel  
Covers: Carbon Steel  
Sizes: 1/2"NPT to 2" NPT  
Flange: 1/2" through 4"  
Gaskets: Grafoil® / Mylar insert, Neoprene, Teflon®  
Cushions: Grafoil® / Mylar insert, Neoprene, Teflon®  
Paint: Standard  
Hardware: A193 B7 bolting / A194 Gr 2 or 2H nuts

