

PENBERTHY

material specifications

Section 4000
 Material Specification 4607
 Issued 05/00
 Replaces 04/93

For: MULTIVIEW™ Mini Magnetic Gage - MMG

Flag Indicator			
Ref. No.	Part	Standard Materials	Optional Materials
2	Chamber (Standpipe)	316/316L STS ASTM A312 gr. TP 316/316L	304/304L STS ASTM A312 gr. TP 304/304L
3	Stud	STL, Zinc Plated ASTM A193 gr. B7	Consult Factory
4	Nut	STL, Zinc Plated ASTM A194 gr. 2 or 2H Zinc Plate ASTM A153 Class D	Consult Factory
7	Gasket	Grafoil® gr. GHR w/316 STS insert	Consult Factory
125	Lock Washer	STL, Zinc Plated ASTM A194 gr. 2 or 2H Zinc Plate ASTM A153 Class D	Consult Factory
151	Float	316/316L STS ASTM A269 gr. TP 316/316L	Titanium ASTM B265 gr. 5
176	Flange (Vessel Connection)	316/316L STS ASTM A182 gr. TP 316/316L	304/304L STS ASTM A182 gr. TP 304/304L
176A	Flange (end/blind end)	316/316L STS ASTM A182 gr. TP 316/316L	304/304L STS ASTM A182 gr. TP 304/304L

Mini Magnetic Gage Flag Indicator			
Ref. No.	Part	Standard Materials	Optional Materials
80	Clamp	Stainless Steel	None
128	Pin	Non-Magnetic STS	None
250	Indicator Housing	Polysulfone	None