

PENBERTHY

material specifications

Section 4000
 Material Specification 4608
 Issued 05/00
 Replaces 04/93

For: MULTIVIEW™ Top mounted Magnetic Gage - TMMG

Standpipe and Float			
Ref. No.	Part	Standard Materials	Optional Materials
2	Chamber (Standpipe)	316/316L STS ASTM A312 gr. TP 316/316L	304/304L STS ASTM A312 gr TP 304/304L Hastelloy-C276 ASTM B619 Monel ASTM B165 Alloy-20 (Carp. 20Cb3) ASTM B464 Consult Factory
151	Float	316/316L STS ASTM A269 gr. TP 316/316L	Titanium ASTM B265 gr 5 Hastelloy-C276 ASTM B626 Monel ASTM B165 Alloy-20 (Carp. 20Cb3) ASTM B468 Consult Factory
171	Float Tube	316/316L STS ASTM A269 gr. TP 316/316L	Titanium ASTM B265 gr 5 Consult Factory
278	Float Guide	316/316L STS ASTM A276	Consult Factory
176	Flange (Vessel Connection)	316/316L STS ASTM A182 gr. F316/316L	304/304L STS ASTM A182 gr F304/304L Hastelloy-C276 ASTM B574 Monel ASTM B564 Alloy-20 (Carp. 20Cb3) ASTM B462 Consult Factory

Top Mounted Magnetic Gage Flag Indicator			
Ref. No.	Part	Standard Materials	Optional Materials
80	Clamp	Stainless Steel	None
128	Pin	Non-Magnetic STS	None
250	Indicator Housing	Polysulfone	None